

Vertical Laminar Flow Cabinet

Model VS-1300U

Working Principle

First, the air is inhaled through the fan and then filtered by the HEPA filter through the static pressure box. After that the filtered clean air is sent out in the state of vertical or horizontal air flow, so that the operation area continues to reach the 100-level cleanliness under the control of clean air and to ensure the production of environmental cleanliness requirements.

Application Range


The vertical flow clean bench is noisier than horizontal clean bench because its fan is installed at the top. The wind blowing vertically so it is often used in medical engineering to ensure the operator's health.

Vertical laminar flow clean bench is widely used in areas requiring partial cleaning, laboratories, biopharmaceuticals, optoelectronics, microelectronics, hard disk manufacturing and other fields.

Features

1. Adopting arbitrary positioning sliding door system
2. The shell is welded by cold-rolled plates, the surface is electrostatically sprayed, and the work surface is SUS304 brushed stainless steel, which is corrosion-resistant and easy to clean.
3. The lighting and sterilization systems are interlocked safely, and there is a timing function of ultraviolet light
4. Digital display LCD control interface, more user-friendly design
5. The vertical quasi-closed table top and the formation of a downward flow air curtain in the operation room can effectively prevent the input of external air and the operation area is clean
6. Equipped with HEPA filter, with primary filter for preliminary filtration, which can effectively extend the service life of the HEPA filter life span





Parameters

Model	VS-1300U
Clean grade	Grade 100(209 E U.S. Federal)
Number of bacteria	≤0.5per utensil.hour(90mm utensil)
Noise	≤62dB
Power	220V/50HZ
Wind speed	0.25-0.45m/s (slow,medium and fast 3 speeds)
illumination	≥300LX
Working area dimension(W*D*H)	1140*600*700mm
Overall dimension(W*D*H)	1300*760*1760mm
HEPA filter size and quantity	1125*540*50x
Fluorescent/UV lamp specifications and quantity	12Wx / 30Wx
Operator	2 persons