Artist of Science

L3 Split Beam VIS Spectrophotometer

L3 Split Beam VIS Spectrophotometer survey optical system, and blazed holographic gratings. They have outstanding test precision and very competitive prices, and blazed holographic gratings. They have outstanding test precision and very competitive prices. 8-inch color touch-screen, cutting-edge user interface, powerful functions, and easy operation.

With powerful functions, the equipment shows great performance in qualitative and quantitative testing, such as:

- Linear regression
- Time-based kinetics determination
- Detailed spectrum scanning
- Peak / Valley detecting
- Concentration direct reading
- GOTO λ

• Multi-wavelength measurement


The equipment is designed with sophisticated power protection system. With high capacity of internal memory, it can store testing results, scanned images, regression equations and correction data. Therefore, it follows a fast initialization when power on. The instrument can draw curve from fixed wavelength time-based scanning, and linear regression.

With USB COM port the device can be connected to a PC, which can not only enhance theperformance in data testing and spectrum

scanning, but also expand the memory to save more testing results.

Main Features

- Split beam optical system
- Automatic wavelength settings
- 8-inch multi color touch-screen
- Automatic 8 position cuvette holder
- Automatic zero and full scale adjustment
- Equipped with USB port



• Software optional

Specifications

Photometry:	Split Beam
Monochromator Type:	Czerny-Turner
Focal Length:	160mm
Grating:	1200 lines/mm
Detector:	Silicon Photocell
Spectrum Bandwidth:	1.8nm
Wavelength Setting:	8-inch color touch-screen
Wavelength Range:	325-1100nm
Wavelength Accuracy:	±0.5nm
Wavelength Repeatability:	≤0.2nm
Stray Light :	≤0.03%T(at 360nm NaNo2)
Photometric Range:	0.0-200.0% T, -0.301-4.000 A, 0.000-9999 C
Photometric Accuracy:	±0.5% T, ±0.002 Abs (0-0.5A), ±0.004 Abs (0.5-1A)
Photometric Repeatability:	$\leq 0.2\%$ T, 0.001 Abs (0-0.5A), 0.002 Abs (0.5-1A)
Noise:	100% (T) noise $\leq 0.2\%$ (T), 0% (T) noise $\leq 0.1\%$ (T)
Power:	AC220V±22V 50Hz±1Hz ,120W
Packaging Size:	710mm X 590mm X 505mm 0.21M ³ 40kg

Standrad Accessories

- Operation manual lpc
- Power cable 1pc

Optional Accessories

- UV WIN8 Station Pro software lpc
- Cuvette 20mm 30mm 50mm 100mm

- Glass cuvette 10mm 4pcs
- Fuse 2pcs • Cuvette holder 10mm lpc
- Cuvette holder 50mm 100mm

P9 www.drawell.com.cn