

DHP-9020A/B、 DHP-9045A/B DHP-9072A/B、 DHP-9125A/B、 DHP-9210A/B Electric Constant-Temperature Incubator

Features

- The shell is made of high-quality cold-rolled steel and the surface is treated with electrostatic spraying process, which makes it beautiful and elegant in shape, anti-corrosion and durable.
- The studio is made of stainless steel plates or galvanized plates and has undergone anti-corrosion treatment. The height of the shelves is adjustable, and the four corners are semi-circular arcs, which is convenient for cleaning.
- The double-layer tempered glass observation window allows for clear viewing of the test samples inside the chamber. The height of the sample shelves in the working chamber is adjustable, making it convenient to use.
- The microcomputer intelligent digital display temperature control instrument ensures precise temperature control without overshoot and features functions such as timing and over-temperature alarm.
- With excellent heat insulation design, it can operate at high temperatures for a long time, has a long service life, is easy to replace, and achieves the greatest degree of being green, energy-saving and environmentally friendly.
- The high-temperature resistant silicone rubber sealing strip is adopted, along with a lockable door lock with adjustable tightness, to ensure good sealing performance and prevent heat loss.
- The unique clean geometric cavity design ensures active and perfect protection of the sample.



DHP-9125A/B DHP-9210A/B



DHP-9045A-DHP-9072A-DHP-9020A

Specifications

Model	DHP-9020A/B	DHP-9045A/B	DHP-9072A/B	DHP-9125A/B	DHP-9210A/B
Capacity	20L	45L	72L	125L	210L
Power supply	220V 50Hz				
Temperature control range	RT+5-65°C				
Temperature resolution	0.1°C				
Temperature fluctuation degree	±0.5°C (at 37°C)				
Inner liner material	A: Galvanized inner liner B: 201 stainless steel inner liner				
Shell material	Galvanized sheet (surface electrostatically sprayed)				
Insulation layer	Ceramic fibers				
Heater	Stainless steel heating tube				
Observation window material	Tempered glass				
Exhaust hole (test hole)	35mm (top) one				
Rated power	180w	200w	300w	400w	500w
Timer	0-9999min				
Operating function	Fixed-value operation, timed operation, automatic stop				
Inner liner dimensions (mm)	260×280×280	360×350×350	400×400×450	450×500×550	500×600×700
Dimensions (mm)	440×415×585	540×500×710	580×540×810	660×630×1055	720×735×1200
Packaging dimensions (mm)	490×520×710	550×600×790	600 × 640× 880	720×700×1125	745×780×1250
Standard/Maximum Spacer	2/4	2/4	2/4	2/6	2/8
Supporting plate	16kg				